

RED SEA BUNKERING

Djibouti Free Zone, LOB 120

PO Box 494, Djibouti

Tel: +253 21 358 737

Email: sales@rsbunkering.com

**RED SEA BUNKERING****VERY LOW SULPHUR FUEL OIL 0.5% ISO 8217:2010 STANDARDS**

PARAMETER	UNIT	LIMIT	GUARANTEED
Density at 15 °C	kg/m ³	Max	991
Viscosity at 50 °C	mm ² /s	Max	380
Water	% V/V	Max	0.50
Micro Carbon Residue	% m/m	Max	18.0
Sulphur	% m/m	Max	0.50
Total Sediment by hot filtration	% m/m	Max	0.10
Sodium	mg/kg	Max	100
Ash	% m/m	Max	0.10
Vanadium	mg/kg	Max	350
Aluminium + Silicon	mg/kg	Max	60
CCAI	-	Max	870
Flash point	°C	Min	60
Pour point in Summer	°C	Max	30
Pour point in Winter	°C	Max	30
Acid number	mg KOH/g	Max	2.5
Hydrogen sulphide	mg/kg	Max	2.0
Used lubricating oils (ULO): Calcium and Zinc; or Calcium and Phosphorus (mg/kg)	The fuel shall be free from ULO. A fuel shall be considered to contain ULO when either one of the following conditions is met: calcium > 30 and zinc > 15; or calcium > 30 and phosphorus > 15		